




Data Sheet DB 100/P



UL Certification	File Nr. E502533 for category QEUY2/8 for use below 1000V File Nr. E502534 for category DLAR2/8 for use above 1000V
Material	Polyester material reinforced with fiberglass BMC RF 3/20
Operating Temperature	°C: - 40° + 130°
Fire reaction	UL94-V0 File Nr. E205214 HL2 according to the EN45545-2
Thread Material	Galvanized Steel
H	101 mm
D1	52 mm
D2	65 mm
E	M10: 20 mm / M12: 19 mm / M16: 23 mm
Tightening Torque	M10: 26 Nm / M12: 36 Nm / M16: 50 Nm
Operating Voltage	8000 V
A.C. surface flashover voltage	30 KV
A.C. internal flashover voltage	50 KV
Tensile stress	2.950 DN
Cantilever stress	1.550 DN
Compressive stress	16.700 DN
Twisting stress	14,5 DN x mm
Package	4 pcs
Weight of package	2,30 kgs

ERIM SRL

Via Bovisasca 24/26 - 20026 - Novate Milanese (MI) - Italy

Tel. (+39) 02/39100533 – Fax. (+39) 02/49698772 – info@erim.it – www.erim.it

P.I./C.F. IT 01803920154 – R.E.A. MI N. 875797 – Reg. Imp. N. 158589 Trib. MI

Cod. SDI SUBM70N