




Data Sheet DB 35/P



UL Certification	File Nr. E502533 for category QEUY2/8 for use below 1000V
	File Nr. E502534 for category DLAR2/8 for use above 1000V
Material	Polyester material reinforced with fiberglass BMC RF 3/20
Operating Temperature	°C: - 40° + 130°
Fire reaction	UL94-V0 File Nr. E205214
	HL2 according to the EN45545-2
Thread Material	Galvanized Steel
H	35,5 mm
D1	35 mm
D2	41 mm
E	M 6 M 8 and M 10 : 10 mm
Tightening Torque	M6: 12 Nm / M8: 20 Nm / M10: 26 Nm
Operating Voltage	1000 V
A.C. surface flashover voltage	10 KV
A.C. internal flashover voltage	30 KV
Tensile stress	1.100 DN
Cantilever stress	800 DN
Compressive stress	8.000 DN
Twisting stress	9 DN x mm
Package	36 pcs
Weight of package	3,60 kgs

ERIM SRL

Via Bovisasca 24/26 - 20026 - Novate Milanese (MI) - Italy

Tel. (+39) 02/39100533 – Fax. (+39) 02/49698772 – info@erim.it – www.erim.it

P.I./C.F. IT 01803920154 – R.E.A. MI N. 875797 – Reg. Imp. N. 158589 Trib. MI

Cod. SDI SUBM70N